



Midwest Geological
Sequestration Consortium

Lessons Learned from the Illinois Basin – Decatur Project: Integration of Deep Saline CO₂ Storage into the Value Change

Sallie E. Greenberg, Ph.D.
Advanced Energy Technology Initiative
University of Illinois – Illinois State Geological Survey

12 May 2015 – CO2GeoNet – Venice, Italy





Acknowledgements

The Midwest Geological Sequestration Consortium is funded by the U.S. Department of Energy through the National Energy Technology Laboratory (NETL) via the Regional Carbon Sequestration Partnership Program (contract number DE-FC26-05NT42588) and by a cost share agreement with the Illinois Department of Commerce and Economic Opportunity, Office of Coal Development through the Illinois Clean Coal Institute.

The Midwest Geological Sequestration Consortium (MGSC) is a collaboration led by the geological surveys of Illinois, Indiana, and Kentucky, USA

Landmark Graphics software via University Donation Program and Petrel* E&P software platform via Schlumberger Carbon Services are gratefully acknowledged



*Mark of Schlumberger



Acknowledgements



The Industrial Carbon Capture and Storage (ICCS) project is administered by the U.S. Department of Energy's Office of Fossil Energy and managed by the National Energy Technology Laboratory (award number DE-FE-0001547) and by a cost share agreement with the Archer Daniels Midland Company, University of Illinois, Schlumberger Carbon Services, and Richland Community College.

This ICCS project received DOE funding from the American Recovery and Reinvestment Act of 2009 (\$141.4 million).






ADM - Decatur CCS Projects

Illinois Basin - Decatur Project


- Large scale geologic test to inject 1.0 million mt of CO₂ over a three year period (1,000 MT/day).

Illinois Industrial CCS Project

- Target & demonstrate advanced CCS technologies at industrial scale facilities.
- Inject and store 1.0 million mt CO₂ per year (3,000 tons/day).
- Study the interaction of two separate plumes.



Illinois Industrial Carbon Capture & Storage (ICCS) Project



Class VI permit issued Sept 24, 2014

~800 meters

North

VV2

GM2

CCS2

NSEC

Richland Community College

VV1

GM1

CCS1

IBDP Wells (**Series 1**) and ICCS wells (**Series 2**) at ADM in Decatur, Illinois

Illinois Basin – Decatur Project Site (on ADM industrial site)

- A** Dehydration/ compression facility location
- B** Pipeline route (1.9 km)
- C** Injection well site
- D** Verification/ monitoring well site
- E** Geophone well





Operational Injection: 17 November 2011

- **IBDP** fully operational 24/7
- **IBDP** is the first 1 million tonne carbon capture and storage project from a biofuel facility in the US
- Injection completed November 2014
- Intensive post-injection monitoring under MGSC through 2017


Total Injection
(26 November 2014):
999,215 tonnes

Injection Well Completion 2009



Packer @ 6,365 ft (1,929 m)

10% Porosity Cutoff



Perforations: 6,985 - 7,015; 7,025 - 7,050
55 ft (16.7 m) open interval

Base of Mount Simon

TD=7236

IBDP Environmental Monitoring Framework

Near Surface

Deep Subsurface

Atmos.

**Soil and
vadose
zone**

**Shallow
ground
water**

**Above
seal**

**Injection
zone**

**Eddy
covariance**

**Meteorological
conditions**

Ambient CO₂

**Tunable diode
laser for CO₂**

**CIR aerial
imagery**

InSAR and GPS

Soil gases

Soil CO₂ flux

**Tunable diode
laser for CO₂**

**Geophysical
surveys**

**Geochemical
sampling**

P/T monitoring

**Geophysical
surveys**

**Geochemical
sampling**

P/T monitoring

**Geophysical
surveys**



**Geochemical
sampling**

P/T monitoring



Outcome: We Better Understand Depositional and Diagenetic History of a Major Storage Resource

- At 500 m in total thickness at Decatur, the Mount Simon Sandstone has been shown to be a substantial storage resource meeting criteria of injectability and storage capacity
- Storage capacity of 11 (P_{90}) to 150 (P_{10}) billion metric tons have been assessed for the entire Illinois Basin
- Intervals of tens of meters of exceptional reservoir quality in the Lower Mount Simon show a combination of primary and secondary porosity in a sand-rich fluvial system
- Original depositional units are well-connected as flow units based on pressure response in the injection and verification wells

Mount Simon Depositional Analogue: Brahmaputra River System



3D Seismic Defines Reservoir




Eroded Precambrian surface

from Leetaru, ISGS

Outcome: We Better Understand Reservoir Fluid Distribution and Impacts of Heterogeneity on Pressure


- Pulsed neutron logs (Schlumberger RST* Log) help estimate the depth, thickness and saturation of CO₂ around injection and verification wells and arrival time at verification well
- CO₂ reached verification well in March 2012 in Zone 3 and July 2012 in Zone 2, much sooner than expected
- Revised reservoir simulation, including permeability distribution, was calibrated to CO₂ arrival at VWI
- Pressure distribution in lower Mt. Simon shows rapid in-zone response to injection variations



Repeat Pulsed Neutron* Logging has Defined CO₂ Distribution at the Injection and Observation Wells

CCS1

VW1




Pre-injection


Five post-injection logging runs:
March, July, and November 2012;
July 2013; July 2014

*Schlumberger Reservoir Saturation Tool (RST)

Westbay* Pressure Monitoring Output – 28 February 2015




Mudstone Baffle Between Injection Zones



6,863-6,863.25
Porosity: 1.5%
 K_v : <0.01 mD
 K_h : 4.13 mD in siltstone laminae

Zone 5




Three 3D Vertical Seismic Profiles Acquired

3D VSP Survey Name	Survey Date	Ground Conditions	Vibrator Sweep	Repeated Shots	Volume of CO ₂ Injected
Baseline 1 (B1)	January 2010	Wet	2 – 100 Hz		
Baseline 2 (B2)	April 2011	Dry	8 – 120 Hz		0
Monitor 1 (M1)	February 2012	Frozen dry	8 – 120 Hz	467	~74,000 tonnes
Monitor 2 (M2)	April 2013	Damp	8 – 120 Hz	385	~433,000 tonnes
Monitor 3 (M3)	February 2014	Frozen	8 – 120 Hz	384	~730,000 tonnes

Outcome: Microseismic Activity Has Supported Insight Into Reservoir Pressure Distribution

- Microseismic activity started only after injection began at site
- Clusters north of injection well first to occur and lie over Precambrian topography that may have localized planes of weakness due to compaction
- Cluster orientation consistent with northeast principal stress direction
- No pre-existing fault planes seen in 3D seismic
- Timing of events ties to pressure propagation
- Most events are in the pre-Mt. Simon and Precambrian basement; none are above the lower Mt. Simon




Microseismic Events Began in January 2012


- June-August 2013: average 89 located events/month
- Mean moment magnitude = -0.98
- Max. event for three months: +0.25
- Recent max event = +1.02 in September 2013

December 2014:
 - Peak frequency at -1.2
 - Peak MM at -0.05

from Schlumberger Carbon Services




Microseismic Cluster Activity: Cluster Locations in Relation to Surface Features



Microseismic Locations

- Dec 15, 2011 – Nov 30, 2014
- Dec 1, 2014 – Dec 31, 2014



Microseismic Cluster Activity: Relationship to Basement Structure

from Schlumberger Carbon Services

Key Operational Results – IBDP at Completion of Injection

- Mount Simon Sandstone reservoir accepted CO₂ more easily than expected resulting in quicker detection at verification well
- Upward plume growth limited by reservoir permeability stratification, as modeled, and confirmed by pressure observations
- Resulting plume believed thinner than expected and was not detected with a 3D vertical seismic profile until April 2013
- Mt. Simon 200,000 ppm brine is more corrosive than expected
- With 999,215 tonnes injected, CO₂ remains in lowermost Mt. Simon; internal reservoir heterogeneity affecting CO₂ distribution
- No CO₂ leakage or adverse impacts detected to date
- Second project (ICCS) will add opportunity to monitor two plumes

CCSI Transition from IEPA Class I to USEPA Class VI

- Injection period covered under IEPA Class I
- Post injection site care covered under USEPA Class VI
 - CCSI becomes monitoring well for CCS2
 - Direct ground water quality monitoring
 - Indirect ground water quality monitoring
 - Mechanical integrity testing (MIT)
 - Plume monitoring
 - Seismic monitoring
 - Pressure-front monitoring
- Interim phase between end of IBDP/CCSI injection and start of CCS2 injection

Direct Ground Water Monitoring Above Eau Claire

- Formations:
 - Quaternary and/or Pennsylvanian
 - St. Peter
 - Ironton-Galesville
- Activity:
 - Fluid sampling
 - Distributed temperature sensing (DTS)
 - Pressure/temperature monitoring (SP and IG)
- Wells: Shallow groundwater, CCS1, CCS2, GM2, VW1, and VW2
- Frequency (changes over time):
 - Interim period
 - CCS2 injection phase
 - CCS2 post-injection phase

Final Steps: Demonstration of Non-Endangerment

At end of PISC period:

- Operator submits a demonstration of non-endangerment of USDW to UIC Program Director (40 CFR 146.93(b)(2) or (3))
- Based on evaluation of site monitoring data in conjunction with computational model
- Uses site-specific conditions to confirm and demonstrate non-endangerment
- Includes:
 - Summary of existing monitoring data
 - Comparison of monitoring data and model predictions and model documentation
 - Evaluation of CO₂ plume
 - Evaluation of mobilized fluids
 - Evaluation of reservoir pressure
 - Evaluation of potential conduits for fluid movement
 - Evaluation of passive seismic data



MGSC



TM



Midwest Geological Sequestration Consortium

www.sequestration.org

sallieg@illinois.edu



ILLINOIS STATE
GEOLOGICAL SURVEY
PRAIRIE RESEARCH INSTITUTE


Photo credits: Daniel Byers

Plume Monitoring

Target Formation	Monitoring Activity	Monitoring Location	Frequency: Interim Period	Frequency: CCS2 Injection Phase	Frequency: CCS2 Post-Injection Phase
<i>Direct Plume Monitoring</i>					
Mt. Simon	Fluid Sampling	VW1	Once	Year 1-3: Annual Year 4-5: None	None
Mt. Simon	Fluid Sampling	VW2	None	Annual	Annual
<i>Indirect Plume Monitoring</i>					
Mt. Simon	Pulse Neutron logging/ RST	VW1 VW2	Once	Year 2, Year 4	Year 1, 3, 5, 7, 10
Mt. Simon	Pulse Neutron logging/ RST	CCS1 CCS2	Once	Year 2, Year 4	Year 1, 3, 5, 7, 10

Seismic Monitoring

Timing		Survey	Extent/Coverage/Resolution
CCSI Injection Phase	2009	Baseline 3D Surface Seismic Survey	Extent = 2,600 Acres Fold Coverage = 2,000 Acres
	2011	Baseline 3D Surface Seismic Survey	Extent = 2,600 Acres Fold Coverage = 2,000 Acres
	2011	Baseline GMI 3D VSP	Resolution = 30 Acres
	2012	GMI 3D VSP	Resolution = 30 Acres
	2013	GMI 3D VSP	Resolution = 30 Acres
	2014	GMI 3D VSP	Resolution = 30 Acres
CCSI Post- Injection Phase	2015	Expanded 3D Surface Seismic Survey	Extent = 3,000 Acres Fold Coverage = 2,200 Acres
	2020	Time Lapse Surface Seismic Survey	Extent = 2,000 Acres Fold Coverage = 600 Acres
	2030	Time Lapse Surface Seismic Survey	Extent = 2,000 Acres Fold Coverage = 600 Acres



Pressure-Front Monitoring

Target Formation	Monitoring Activity	Monitoring Location	Frequency: Interim Period	Frequency: CCS2 Injection Phase	Frequency: CCS2 Post-Injection Phase
Mt. Simon	Pressure/ temperature monitoring	VW1	Continuous	Y1-3: Continuous Y 4-5: None	None
		VW2	None	Continuous	Continuous
		CCS1	Continuous	Continuous	Y 1-3: Continuous Y 4-10: Annual
		CCS2	None	Continuous	Y 1-3: Continuous Y 4-10: Annual
Mt. Simon	DTS	CCS1	Continuous	Continuous	Y 1: Continuous Y 2-10: None
		CCS2	None	Continuous	Y 1: Continuous Y 2-10: Annual
Multiple	Passive seismic (detect M 1.0 events)	Borehole & surface seismic stations within AoR	None	Continuous	Continuous